INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 1,0-PUR 0,007 OBS 1097237 PHOENIX CONTACT Sensor/actuator cable, 4-position, PUR halogen-free,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,0-PUR 0,07 OBS

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 1,0-PUR 0,07 OBS
Catalog number	1097237
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2F890722DE
Generated	2026-11-18

Product Overview

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on free cable end, cable length: 1 m, Customer version
Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight male connector M12, coding: A, to free cable end, cable length: 1 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1097237
Packing unit 1
GTIN 4055626938271
Custom tariff number 85444290
Drawings
Ambient conditions
Cable
Dimensions
General

Classifications
Drawings
Cable cross section
PUR halogen-free black [PUR]
Back to topDimensions
Length of cable 1 m
Back to topAmbient conditions
Degree of protection IP65
IP67
Back to topGeneral
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Overvoltage category II
Degree of pollution 3
Torque 0.4 Nm
Back to topCable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 4.2 mm ±0.15 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Number of bending cycles 10000000
Minimum bending radius, drag chain applications 10 x D
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 30 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance >= 1 G?*km
Conductor resistance <= 58 ?/km
Nominal voltage, cable <= 300 V
Test voltage,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,0-PUR 0,07 OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.