INDUSTRIAL COMPONENT DATA

# SAC-4P-M12MS/10,0-BF145 1410074 PHOENIX CONTACT Sensor/actuator cable SAC-4P-M12MS/10,0-BF145 1410074

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/10,0-BF145**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SAC-4P-M12MS/10,0-BF145 |
| Catalog number | 1410074 |
| Category | Sensor-actuator patch cord |
| Minimum order | 25 Pcs |
| Document ID | EO-9046321413 |
| Generated | 2026-11-19 |

## Product Overview

Sensor/actuator cable - SAC-4P-M12MS/10,0-BF145 - 1410074
Sensor/actuator cable, halogen-free POC, irradiation cross-linked, black RAL 9005, M12 straight male connector, coding: A, to free cable end, cable length: 10 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |

## Additional Product Information

Sensor/actuator cable, POC halogen-free, irradiated, black RAL 9005, Plug straight M12, A-coded, on free cable end, cable length: 10 m
Key Commercial Data
Orderkey 1410074
Packing unit 1
GTIN 4046356887359
Custom tariff number 85444290
Dimensions
Length of cable 10 m
Ambient conditions
Degree of protection IP65
IP67
General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Cable
Cable type POC irradiated halogen-free black
Cable type (abbreviation) BF 145
Conductor cross section 4x 0.75 mm²
AWG signal line 18
Core diameter including insulation 2.2 mm
Wire colors black 1, black 2, black 3, black 4
Overall twist 4 wires around filler to the core
External sheath, color black RAL 9005
External cable diameter D 6.9 mm
Minimum bending radius, fixed installation 4 x D
Minimum bending radius, flexible installation 8 x D
Cable weight 75 kg/km
Outer sheath, material POC
Material conductor insulation POC
Conductor material Tin-plated Cu litz wires
Nominal voltage, cable 300 V
Test voltage, cable 3500 V
Special properties Irradiated
Flame resistance according to IEC 60332-1
according to EN 50265-2-1
Halogen-free according to IEC 60754-1
According to EN 50267-2-1
Concentration of fumes in accordance with IEC 61034
EN 50268-2
Ambient temperature (operation) -55 °C ... 145 °C (cable, fixed installation)
-35 °C ... 120 °C (cable, flexible installation)
Classifications
eCl@ss
eCl@ss 4.0 2706...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/10,0-BF145 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.