INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-140 1504864 PHOENIX CONTACT Data cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-140

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-140
Catalog number	1504864
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-EB2944B5E3
Generated	2026-11-18

Product Overview

Data cable
Data cable, 4-pole, Straight M12 connector, coding: A, to free cable end, cable length: 5 m
Data cable, 4-pole, PUR/PVC, yellow, M12 straight connector, coding: A, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1504864
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4017918845544
Weight per Piece (excluding packing) 198.940 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 5 m
Ambient conditions
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR/PVC yellow
Cable type (abbreviation) 140
Cable abbreviation LiYY-11Y
UL AWM style 20549
Conductor cross section 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.5 mm ±0.05 mm
Thickness, insulation approx. 0.3 mm (Core insulation)
>= 0.38 mm (Outer cable sheath)
approx. 0.35 mm (Inner sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color yellow
External cable diameter D 5.2 mm ±0.2 mm
Smallest bending radius, fixed installation 52 mm
Smallest bending radius, movable installation 52 mm
Number of bending cycles 2000000
Bending radius 52 mm
Traversing path 5 m
Traversing rate 3 m/s
Cable weight 39 kg/km
Outer sheath, material PUR
Material, inner sheath PVC
Material conductor insulation PVC
Conductor material Bare C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-140 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.