INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 7,0-PVC/M12FR 1447222 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 7,0-PVC/M12FR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 7,0-PVC/M12FR
Catalog number	1447222
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-73E4656E1C
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, PVC, black RAL 9005

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1447222
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356678698
Weight per Piece (excluding packing) 261.100 g
Custom tariff number 85444290
Country of origin DE (Germany)
General
Rated voltage 250 V AC
250 V DC
Cable
Cable type PVC black

Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section 4x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 19x 0.15 mm
Core diameter including insulation 1.26 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black RAL 9005
Outer sheath thickness >= 0.76 mm
External cable diameter D 4.7 mm ±0.15 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Cable weight 40 kg/km
Outer sheath, material PVC
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance >= 200 M?*km (at 20 °C)
Conductor resistance <= 57 ?/km (at 20 °C)
Nominal voltage, cable <= 300 V
Test voltage, cable >= 3000 V
Ambient temperature (operation) -40 °C ... 80 °C (cable, fixed installation)
-25 °C ... 80 °C (cable, flexible installation)
Classifications
eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.119030300eCl@ss 6.027061800eCl@ss 7.027061801eCl@ss 8.027061801eCl@ss 9.027061801
ETIM 3.0EC001855ETIM 4.0EC001855ETIM 5.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 7,0-PVC/M12FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.