INDUSTRIAL COMPONENT DATA

SAC-4P-M12MSS/5-PUR/FRS PE SH 1065585 PHOENIX CONTACT Power cable, 4-position, PUR halogen-free, orange RAL ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MSS/5-PUR/FRS PE SH

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MSS/5-PUR/FRS PE SH
Catalog number	1065585
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3E60344006
Generated	2026-11-19

Product Overview

Power cable, 4-position, PUR halogen-free, orange RAL 2003, shielded (Advanced Shielding Technology), Plug straight M12, S-coded, on Socket angled M12, S-coded, cable length: 5 m, for AC current up to 12 A/690 V
Power cable, 4-pole halogen-free, shielded (Advanced Shielding Technology), Straight connector M12, coding: S, to Elbowed Female M12, coding: S, cable length: 5 m, for alternating current up to 12 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1065585
Packing unit 1
GTIN 4055626728414
Custom tariff number 85444290
Drawings
Ambient conditions
Material
Cable
Classifications

Dimensions
General
Standards and Regulations
Environmental Product Compliance
Drawings
Dimensional drawing
Plug, M12 x 1, straight, shielded
Dimensional drawing
M12 x 1 socket, angled
Circuit diagram
Contact assignment of the M12 plug
Schematic diagram
M12 plug pin assignment, 4-pos., S-coded, plug side view
Schematic diagram
Pin assignment of M12 socket, 4-pos., S-coded, socket side view
Cable cross section
PUR halogen-free orange shielded [PUR]
Back to topDimensions
Length of cable 5 m
Back to topAmbient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP65
IP67
Back to topGeneral
Rated current at 40°C 12 A
Rated voltage 690 V AC
Number of positions 4
Color handle area black
Insulation resistance >= 100 M?
Coding S power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Torque 0.4 Nm (M12 connector)
Back to topMaterial
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PP
Material, knurls Zinc die-cast, nickel-plated
Back to topStandards and Regulations
Standards/specifications M12 connector IEC 61076-2-111
Flammability rating according to UL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MSS/5-PUR/FRS PE SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.