INDUSTRIAL COMPONENT DATA

SAC-4P-M12MST/ 1,0-110/M12FST 1089988 PHOENIX CONTACT Power cable, 4-position, PVC, black-gray RAL 7021, Plu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MST/ 1,0-110/M12FST



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MST/ 1,0-110/M12FST
Catalog number	1089988
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-FF84295D71
Generated	2026-11-19

Product Overview

Power cable, 4-position, PVC, black-gray RAL 7021, Plug straight M12, T-coded, on Socket straight M12, T-coded, cable length: 1 m, For direct current up to 12 A/63 V
Power cable, 4-pole, M12 straight connector, encoding: T, to M12 straight female, coding: T, cable length: 1 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1089988
Packing unit 1 pc
Catalog page Page 291 (C-2-2019)
GTIN 4055626898643
Weight per Piece (excluding packing) 140.000 g
Custom tariff number 85444290
Country of origin PL (Poland)
Drawings
Ambient conditions

Material
Cable
Classifications
Dimensions
General
Standards and Regulations
Environmental Product Compliance
Drawings
Dimensional drawing
Plug, M12 x 1, straight
Dimensional drawing
M12 x 1 socket, straight
Circuit diagram
Contact assignment of the M12 connector and the M12 socket
Schematic diagram
Pin assignment for M12 plug, 4-pos., T-coded, view of plug side
Schematic diagram
Pin assignment of M12 socket, 4-pos., T-coded, socket side view
Cable cross section
PVC black [110]
Back to topDimensions
Length of cable 1 m
Back to topAmbient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP65
IP67
Back to topGeneral
Rated current at 40°C 12 A
Rated voltage 63 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding T power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Back to topMaterial
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PP
Material, knurls Zinc die-cast, nickel-plated
Back to topStandards and Regulations
Standards/specifications M12 con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MST/ 1,0-110/M12FST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.