INDUSTRIAL COMPONENT DATA

SAC-4P-M12Y/28X-9XM12F OD RI 1421454 PHOENIX CONTACT Sensor/actuator cable SAC-4P-M12Y/28X-9XM12F OD RI 1421..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12Y/28X-9XM12F OD RI

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12Y/28X-9XM12F OD RI
Catalog number	1421454
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-9F8B6D0B17
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-4P-M12Y/28X-9XM12F OD RI - 1421454
Sensor/Actuator Cable, 4-Pole, Halogen-Free, PE-X, Grey-Black RAL 7021, M12 Straight Male Connector, A, A Encoding: A, A Straight Male M12, Coding: A, M12 Y-Distributor, Outdoor Application, with Stainless Steel Knurling
Sensor/Actuator Cable, 4-Pole, Halogen-Free PE-X, Grey-Black RAL 7021, M12 Straight Connector, A, to M12 Straight Connector, A-Coding, M12 Y-Distributor, Outdoor Application, with Stainless Steel Knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 4-position, PE-X halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Plug straight M12, A-coded, M12 Y-distributor, for outdoor applications, with high-grade steel knurl
Key Commercial Data
Orderkey 1421454
Packing unit 1
GTIN 4055626263922
Custom tariff number 85444290
Ambient conditions
Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)

-40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4))
120 °C (at 48 h - see test report 19233)
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FPM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 V0
Cable
Cable type PE-X black
Cable type (abbreviation) 28X
Cable abbreviation Li2X2X
Conductor cross section 4x 0.5 mm² (Signal line)
AWG signal line 20
Conductor structure signal line 28x 0.15 mm
Core diameter including insulation 1.6 mm ±0.05 mm (Signal line)
Thickness, insulation approx. 0.3 mm (...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12Y/28X-9XM12F OD RI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.