INDUSTRIAL COMPONENT DATA

SAC-4P-M8MR/ 2,0-542 BK 1406214 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M8MR/ 2,0-542 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M8MR/ 2,0-542 BK
Catalog number	1406214
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-710CD07E6F
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, PVC, yellow, M8 angled male connector, to free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1406214
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356798365
Weight per Piece (excluding packing) 81.400 g
Custom tariff number 85444290
Country of origin US (United States)
Dimensions
Length of cable 2 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.2 Nm (M8 connectors)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC yellow 105 °C
Cable type (abbreviation) 542
UL AWM style 2517 (105 °C / 300 V)
AWG signal line 24
Conductor structure signal line 32x 1.10 mm
Core diameter including insulation 1.12 mm ±0.03 mm
Wire colors brown, blue, black, white
Overall twist 4 wires, twisted
External sheath, color yellow
External cable diameter D 4.4 mm ±0.2 mm
Minimum bending radius, flexible installation 8 x D
Cable weight 25 kg/km
Outer sheath, material PVC
Material conductor ins...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M8MR/ 2,0-542 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.