INDUSTRIAL COMPONENT DATA

SAC-4P-M8MR/ 5,0-542 SH BK 1406013 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M8MR/ 5,0-542 SH BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M8MR/ 5,0-542 SH BK
Catalog number	1406013
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-607050F514
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, PVC, yellow, shielded, M8 angled male connector, to free cable end, cable length: 5 m
Sensor/actuator cable, 4-position, PVC, yellow, shielded, Plug angled M8, on free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Application Standard, U.S. cables
Number of positions 4
No. of cable outlets 1
Shielded yes
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Outer sheath, material PVC
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.2 Nm (M8 connectors)
ConnectorConnection 1
Type Plug angled M8
Connection 2
Type free cable end
Cable/lineCable length 5 m
PVC yellow 105 °C [542]
Dimensional drawing
Cable weight 37 kg/km
UL AWM Style 2517 (105 °C / 300 V)
Number of positions 4
Shielded yes
Cable type PVC yellow 105 °C [542]
Conductor structure signal line 32x 1.10 mm
AWG signal line 24
Wire diameter incl. insulation 1.12 mm ±0.03 mm
External cable diameter 4.90 mm ±0.2 mm
Outer sheath, material PVC
External sheath, color yellow
Conductor material Tin-plated Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, black, white
Overall twist 4 wires, twisted
Optical shield....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M8MR/ 5,0-542 SH BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.