INDUSTRIAL COMPONENT DATA

SAC-4P-MRDC1/2,0-936/MRDC4 SCO 1443077 PHOENIX CONTACT Sensor/actuator cable SAC-4P-MRDC1/2,0-936/MRDC4 SCO ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MRDC1/2,0-936/MRDC4 SCO

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MRDC1/2,0-936/MRDC4 SCO
Catalog number	1443077
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-04FFCB12C9
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-4P-MRDC1/2,0-936/MRDC4 SCO - 1443077

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 4-position, PE-X halogen-free, black RAL 9005, Plug angled M12 SPEEDCON, on free cable end, cable length: 2 m
Key Commercial Data
Orderkey 1443077
Packing unit 1
GTIN 4046356538015
Custom tariff number 85444290
Dimensions
Length of cable 2 m
General
Rated voltage 48 V AC
60 V DC
Number of positions 4

Cable
Cable type Ethernet
Cable type (abbreviation) 936
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.95 mm
Wire colors white-blue, orange-yellow
Overall twist Star quad
Shielding Plastic-coated aluminum foil, tinned copper braided shield
Optical shield covering 100 %
External sheath, color black RAL 9005
Outer sheath thickness >= 0.8 mm
External cable diameter D 7.25 mm ±0,3 mm
Minimum bending radius, fixed installation 6 x D
Minimum bending radius, flexible installation 10 x D
Cable weight 81 g/m
Outer sheath, material PE-X
Material conductor insulation PE-X
Conductor material silver-plated Cu litz wires
Conductor resistance <= 54.4 ?/km
Working capacitance <= 65 pF (core-core)
<= 100 pF (core-shield)
Wave impedance 100 ? ±5 ? (f = 100 MHz)
Near end crosstalk attenuation (NEXT) 80 dB (with 1 MHz)
76 dB (at 4 ?Hz)
67 dB (at 10 MHz)
60 dB (at 31.5 ?Hz)
56 dB (at 62.5 ?Hz)
53 dB (at 100 MHz)
Attenuation 2 dB (with 1 MHz)
4 dB (at 4 ?Hz)
6.5 dB (at 10 MHz)
10.5 dB (at 31.5 ?Hz)
14 dB (at 62.5 ?Hz)
18 dB (at 100 MHz)
Return Loss 35 dB (at 4....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MRDC1/2,0-936/MRDC4 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.