INDUSTRIAL COMPONENT DATA

SAC-4P-MS/1,6-240 SCO 1410491 PHOENIX CONTACT Sensor/actuator cable SAC-4P-MS/1,6-240 SCO 1410491

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MS/1,6-240 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MS/1,6-240 SCO
Catalog number	1410491
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-C913EC9B84
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-4P-MS/1,6-240 SCO - 1410491
Sensor/actuator cable, 4-position, PUR halogen-free, yellow, Plug straight M12 SPEEDCON, coding: A, on free cable end, cable length: 1.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Application Standard
Number of positions 4
No. of cable outlets 1
Shielded no
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type Plug straight M12 SPEEDCON
Number of positions 4
Locking type SPEEDCON
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 1.6 m
PUR halogen-free yellow [240]
Dimensional drawing
Cable weight 30 kg/km
Number of positions 4
Shielded no
Cable type PUR halogen-free yellow [240]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm²
Wire diameter incl. insulation 1.27 mm ±0.02 mm
External cable diameter 4.70 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color yellow
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation >=...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MS/1,6-240 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.