INDUSTRIAL COMPONENT DATA

UCS 145-125-H-GD 7035 2203334 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS 145-125-H-GD 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS 145-125-H-GD 7035
Catalog number	2203334
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-54CB8A6293
Generated	2026-11-19

Product Overview

Electronic housing
Complete housing for printed circuit boards, flexible positioning; includes the halves of the housing, closed side walls, adhesion domes for fixing the plate, screws for housing and fixing the plate; light grey housing colour with turquoise blue angular inserts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203334
Packing unit 1 pc
GTIN 4055626404462
Weight per Piece (excluding packing) 446.000 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Type UCS 145-125-H-GD 7035
Order No. 2203334
Housing type Universal housings
Type high

Measurements
Dimensional drawing
Width [w] 145 mm
Height [h] 125 mm
Depth [d] 67 mm
Dimensions 120 mm x 100 mm (Maximum circuit board dimensions)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material PC
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
PCB data
Number of PCB holders 1
Note on PCB holders This product is prepared for a printed-circuit board. Additional printed-circuit boards can be mounted using adhesive pads (accessories).
PCB thickness 0.8 mm ... 3 mm
Total PCB surface 12000 mm²
Type of PCB mount Bolt mounting
Power dissipation, single housing at 20°C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 13.5 W
Power dissipation, single housing at 30 °C
Ambient temperature 30 °C
Reduction factor 0.84
Mounting position vertical
Power dissipation 11.3 W
Power dissipation, single housing at 40 °C
Ambient temperature 40 °C
Reduction factor 0.66
Mounting position vertical
Power dissipati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS 145-125-H-GD 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.