INDUSTRIAL COMPONENT DATA

SAC-5,0-PVC/A-LS/0,15PVC/A-LS 1444209 PHOENIX CONTACT Cable for sensors/actuators, 3-pin, PVC, black RAL 900..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5,0-PVC/A-LS/0,15PVC/A-LS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5,0-PVC/A-LS/0,15PVC/A-LS
Catalog number	1444209
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-016E7146A4
Generated	2026-11-19

Product Overview

Cable for sensors/actuators, 3-pin, PVC, black RAL 9005, end of free cable, to valve Connector A, with 1 LED, connected with Z Diode, cable length: 5 m
Sensor/actuator cable, 3-pole, PVC, black RAL 9005, free cable end, to Valve Connector A, with 1 LED, connected with Diode Z, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor-/actorkabel, 3-polig, PVC, zwart, vrij kabeluiteinde management Ventielsteker is The met 1 of the led, voorzien van a-Z-diode, kabellengte: 5 m
Business
The code of the application One million four hundred forty four thousand two hundred nine
The amount of the package (C#) 1 Unit
The minimum quantity of the order 100 Pcs
Note The production is linked to the application (no removal)
GTIN Four trillion forty six billion three hundred fifty six million five hundred twenty five thousand seven hundred thirty two
Weight per piece (excluding packing) 334,500 GRM
The number of corporate and commercial Eighty five million four hundred forty four thousand two hundred ninety

The country-of-origin PL (Poland).
Measures
The length of the cable A 5-m
Environmental conditions
The degree of protection IP67
The general
Rated current at 40 °C Four
Rated voltage THAT IS, 24 V AC
24 V DC
The number of poles in the Three
The resistance of the insulation >= 100 M?
An indication of the state of LED 1
The / - component of the protective Leds Z Z Z Z
Over voltage category II
The degree of impurity, Three
The Material
Class of flammability according to UL 94 Hemoglobin (HB)
Material Contact valve Connector CuSn
Material contact Surface valve Connector Ag
The Material of the female connector of the power plug of the valve PRODUCT
The Material of the box, the connector to the valve PRODUCT
The Material of the sealing The TPU (flat Gasket-connector to the valve)
The rules and the provisions of
Cla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5,0-PVC/A-LS/0,15PVC/A-LS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.