INDUSTRIAL COMPONENT DATA

SAC-5P-10,0-186/FSB SCO 1418709 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-10,0-186/FSB SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-10,0-186/FSB SCO
Catalog number	1418709
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-EF61F9B8BE
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, PUR, greyish black RAL 7021, free cable end, to Straight connection female M12 SPEEDCON, coding: B, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1418709
Packing unit 1
GTIN 4055626145211
Custom tariff number 85444290
Dimensions
Length of cable 10 m
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Coding B-coded

Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR POWER 0.75 mm² black
Cable type (abbreviation) 186
Cable abbreviation LiY11Y
Conductor cross section 5x 0.75 mm² (power line)
AWG signal line 18
Conductor structure signal line 42x 0.15 mm
Core diameter including insulation 1.7 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
>= 0.76 mm (Outer cable sheath)
Wire colors Brown, white, blue, black, gray
Overall twist 5 wires around filler to the core
External sheath, color black-gray RAL 7021
External cable diameter D 6.3 mm ±0.2 mm
Smallest bending radius, movable installation 63 mm
Number of bending cycles 2000000
Bending radius 63 mm
Traversing path 5 m
Traversing rate 3 m/s
Acceleration 5 m/s²
Cable weight 67 kg/km
Outer sheath, material PUR
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance >= 1 M?*km (at 20 °C)
Conductor resi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-10,0-186/FSB SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.