INDUSTRIAL COMPONENT DATA

SAC-5P- 1,2-923/M12FS CAN P 1407865 PHOENIX CONTACT Bus system cable SAC-5P- 1,2-923/M12FS CAN P 1407865

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-1,2-923/M12FS CAN P



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-1,2-923/M12FS CAN P
Catalog number	1407865
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-DFED17CC64
Generated	2026-11-19

Product Overview

Bus system cable - SAC-5P- 1,2-923/M12FS CAN P - 1407865
Bus system cable, CANopen®, 5-pole halogen-free, shielded, free cable end, to straight female M12, coding: A SPEEDCON, cable length: 1.2 m, Unshielded plug-in connector, with plastic knurling
Bus system cable, CANopen®, 5-position, PUR halogen-free, silver-grey RAL 7001, shielded, free cable end, on Socket straight M12 SPEEDCON, coding: A, cable length: 1.2 m, Connector unshielded, with plastic knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
Application Bus system
Sensor type CANopen®
Number of positions 5
No. of cable outlets 1
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
InterfacesBus system CANopen®
Signal type/category CANopen®

SignalingStatus display no
Status display present No
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection PA
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12 SPEEDCON
Number of positions 5
Locking type SPEEDCON
Coding type A (Standard)
Cable/lineCable length 1.2 m
CANopen®/DeviceNet™, PUR, gray [923]
Dimensional drawing
Cable weight 90 kg/km
UL AWM Style 21198 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type CANopen®/DeviceNet™, PUR, gray [923]
Conductor structure 2xAWG24/19+2xAWG22/19
Conductor structure signal line 19x 0.13 mm
AWG signal line 24
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
Wire diameter incl. insulation 1.95 mm ±0.05 mm (Data cable)
1.4 mm ±0.05 mm (Power supply)
External cable diameter 6.70 mm ±0.3 mm
Outer sheath, material PUR
External sheath, color silv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-1,2-923/M12FS CAN P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.