INDUSTRIAL COMPONENT DATA

SAC-5P-20,0-PUR/M12FS 1500376 PHOENIX CONTACT Sensor/actuator cable SAC-5P-20,0-PUR/M12FS 1500376

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-20,0-PUR/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-20,0-PUR/M12FS
Catalog number	1500376
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-14E52A90E6
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-5P-20,0-PUR/M12FS - 1500376
Sensor/Actuator Cable, 5-pole halogen-free, free cable end, to Straight female M12, coding: A, cable length: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 20 m
Key Commercial Data
Orderkey 1500376
Packing unit 5 pc
Minimum order quantity 25 pc
Note Made to Order (non-returnable)
GTIN 4017918590055
Weight per Piece (excluding packing) 673.400 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 20 m
Stripping length of the free conductor end 50 mm

Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation approx. 0.5 mm
Wire colors brown, white, blue,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-20,0-PUR/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.