INDUSTRIAL COMPONENT DATA

SAC-5P-25,0-923/FR CAN SCO 1044464 PHOENIX CONTACT Cable, system bus, CANopen®, 5-pole, PUR halogen-free, gr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-25,0-923/FR CAN SCO

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-25,0-923/FR CAN SCO
Catalog number	1044464
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-417EF9DD26
Generated	2026-11-19

Product Overview

Cable, system bus, CANopen®, 5-pole, PUR halogen-free, gray RAL 7001, shielded, end of free cable, to connection socket angled M12 SPEEDCON, coded, cable length: 25 m, plug-in Connector without shield
Bus system cable, CANopen®, 5-position halogen-free, shielded, free cable end, on Socket angled M12, coding: A SPEEDCON, cable length: 25 m, Connector unshielded

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
Sensor type CANopen®
Number of positions 5
InterfacesSignal type/category CANopen®
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12 SPEEDCON
Number of positions 5
Coding type A (Standard)
Number of positions 5
Locking type SPEEDCON

Cable/lineCable length 25 m
CANopen®/DeviceNet™, PUR, gray [923]
Dimensional drawing
Cable weight 90 kg/km
UL AWM Style 21198 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type CANopen®/DeviceNet™, PUR, gray [923]
Conductor structure 2xAWG24/19+2xAWG22/19
Conductor structure signal line 19x 0.13 mm
AWG signal line 24
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
Wire diameter incl. insulation 1.95 mm ±0.05 mm (Data cable)
1.4 mm ±0.05 mm (Power supply)
External cable diameter 6.7 mm ±0.3 mm
Outer sheath, material PUR
External sheath, color silver-grey RAL 7001
Conductor material Tin-plated Cu litz wires
Material wire insulation Foamed PE (Data cable)
PE (Power supply)
Single wire, color red-black, blue-white
Twisted pairs 2 cores to the pair
Type of pair shielding Plastic-coated aluminum foil, aluminum side outside
Overall twist 2 pairs around a drain wire in the center to the core
Optical shield covering 80 %
Insulation resistance >= 5 G?*km (Data cable)
>= 5 G?*km (Power supply)
Loop resistance <= 181.80 ?/km (Data cable)
<= 114.80 ?/km (Power supply)
Wave impedance 120 ? ±10 % (with 1 MHz)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-25,0-923/FR CAN SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.