INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-186/FRB SCO 1409363 PHOENIX CONTACT Sensor/actuator cable SAC-5P- 5,0-186/FRB SCO 1409363

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P- 5,0-186/FRB SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P- 5,0-186/FRB SCO
Catalog number	1409363
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2F5E8092CB
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-5P- 5,0-186/FRB SCO - 1409363
Sensor/actuator cable, 5-pole, PUR, greyish-black RAL 7021, free cable end, to Angled connection female M12 SPEEDCON, coding: coded B, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR, black-gray RAL 7021, free cable end, on Socket angled M12 SPEEDCON, B-coded, cable length: 5 m
Key Commercial Data
Orderkey 1409363
Packing unit 1
GTIN 4046356870016
Custom tariff number 85444290
Dimensions
Length of cable 5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67

IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding B-coded
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR POWER 0.75 mm² black
Cable type (abbreviation) 186
Cable abbreviation LiY11Y
Conductor cross section 5x 0.75 mm² (power line)
AWG signal line 18
Conductor structure signal line 42x 0.15 mm
Core diameter including insulation 1.7 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
>= 0.76 mm (Outer cable sheath)
Wire colors Brown, white, blue, black, gray
Overall twist 5 wires around filler to the core
External sheath, color black-gray RAL 7021
External cable diameter D 6.3 mm ±0.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P- 5,0-186/FRB SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.