INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-510/M12FSL FE 1424619 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-510/M12FSL FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-510/M12FSL FE
Catalog number	1424619
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-22DC3DAF2B
Generated	2026-11-19

Product Overview

Power cable

Power cable, 5-pole, free cable end, to straight female M12, coding: L, cable length: 5 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1424619
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 299 (C-2-2017)
GTIN 4055626375441
Weight per Piece (excluding packing) 759.430 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 1.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 12 A
Rated voltage 63 V DC
Number of positions 5
Color handle area black
Insulation resistance >= 100 M?
Coding L - Power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PA
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-111
Flammability rating according to UL 94 V0
Cable
Cable type PVC gray
Cable type (abbreviation) 510
UL AWM style 20233 / 10493 (80°C/300 V)
Conductor cross section 5x 1.5 mm²
AWG power supply 16
Conductor structure, voltage supply 78x 0.15 mm
Core diameter including insulation 2.35 mm ±0.05 mm
Thickness, insulation >= 0.25 mm
Wire colors Brown, white, blue, black, gray
External sheath, color gray RAL 7001
Outer sheath thickn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-510/M12FSL FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.