INDUSTRIAL COMPONENT DATA

SAC-5P-5,0-515/M12FS VA E-UL 1031238 PHOENIX CONTACT Cable for sensors/actuators 5-pin, PVC, black RAL 9005,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-515/M12FS VA E-UL

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-515/M12FS VA E-UL
Catalog number	1031238
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-37C33F13F1
Generated	2026-11-19

Product Overview

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, cable length: 5 m, Knurled stainless steel
Sensor/actuator cable, 5-pole, PVC, black RAL 9005, free cable end, to Straight connection female M12, coding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, end of free cable, Female straight connection M12, coded, cable length: 5 m
Data commercial
Key order One million thirty one thousand two hundred thirty eight
Packing unit 1 pcs
Key selling BF1CDA -
Minimum order quantity 50 pcs
EAN Four trillion fifty five billion six hundred twenty six million five hundred thirty four thousand seven hundred fifty six
Unit weight (excluding packaging) 278,500 g
Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety
Measures
Cable length 5 m
Environmental conditions

Room temperature (service) -25 °C ... 90 °C (male / female)
Index of protection IP65
IP67
IP68
IP69K
Overview
Current sizing at 40 °C 4 To
Tension sizing 48 V AC
60 V DC
Number of poles Five
Insulation resistance >= 100 M?
Encoding A - standard
Standards/specifications Plug-in connector M12 to IEC 61076-2-101
Status indication Not
Protective circuit/component protection without connect
Category surge II
Pollution degree Three
Cycles of plug >= 100
Material
Class of flammability according to UL 94 HB
Material contact CuSn
Material contact surface Ni/Au
Material support of contacts TPU GF
Material body grip TPU fire-retardant, self-extinguishing
Material knurled Stainless steel 1.4404
Standards and specifications
Name of standard Plug-in connector M12
Standards/specifications IEC 61076-2-101
Class of flammability according to UL 94 HB
Cable
Type of cable Black PVC 5. Driver gray
Cable type (...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-515/M12FS VA E-UL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.