INDUSTRIAL COMPONENT DATA

SAC-5P-7,5-802/M12FR-3L 1454383 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-7,5-802/M12FR-3L

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-7,5-802/M12FR-3L
Catalog number	1454383
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-AD742F628D
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, halogen-free, solder-resistant, highly flexible, grey RAL 7001, free cable end, to Elbow connection female M12, coding: A, with 3 LEDs, cable length: 7.5 m
Sensor/actuator cable, 5-position, PUR halogen-free, resistant to welding sparks, highly flexible, gray RAL 7001, free cable end, on Socket angled M12, coding: A, with 3 LEDs, cable length: 7.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Number of positions 5
No. of cable outlets 1
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 24 V
Nominal current IN 4 A
SignalingStatus display 3 LEDs
Status display present Yes
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Number of positions 5
Coding type A
Cable/lineCable length 7.5 m
PUR halogen-free highly flexible resistant to welding sparks gray 5th conductor green/yellow [802]
Dimensional drawing
Note Due to the extremely robust outer sheath, this cable should only be stripped in 5 cm increments.
Cable weight 38 kg/km
UL AWM Style 20549
Number of positions 5
Shielded no
Cable type PUR halogen-free highly flexible resistant to welding sparks gray 5th conductor green/yellow [802]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 5x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.3 mm ±0.05 mm (Signal line)
External cable diameter 5.10 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color gray RAL 7001
Conductor material Bare Cu l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-7,5-802/M12FR-3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.