INDUSTRIAL COMPONENT DATA

SAC-5P-M12FR/ 8,0-PUR/M12FR VW 1693869 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12FR/ 8,0-PUR/M12FR VW

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12FR/ 8,0-PUR/M12FR VW
Catalog number	1693869
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-0DD3493D85
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, halogen-free PUR, irradiation cross-linked, orange RAL 2003, Angled connection female M12, coding: A, a Angled connection female M12, coding: A, cable length: 8 m
Sensor/actuator cable, 5-position, PUR halogen-free, irradiated, orange RAL 2003, Socket angled M12, coding: A, on Socket angled M12, coding: A, cable length: 8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Number of positions 5
No. of cable outlets 1
Shielded no
Coding A
Material specificationsContact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU
Electrical propertiesRated voltage in acc. with IEC 61076-2-101 60 V
Nominal voltage UN 48 V AC
60 V DC

Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display present No
ConnectorConnection 1
Type Socket angled M12
Number of positions 5
Coding type A
Connection 2
Type Socket angled M12
Number of positions 5
Coding type A
Cable/lineCable length 8 m
PUR irradiated halogen-free orange [150]
Dimensional drawing
Number of positions 5
Shielded no
Cable type PUR irradiated halogen-free orange [150]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
1x 0.5 mm² (PE connection)
External cable diameter 5.20 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color orange RAL 2003
Conductor material Bare Cu litz wires
Material wire insulation PE
Single wire, color brown, white, blue, black, green-yellow
Overall twist 5 cores, twisted
Max. conductor resistance <= 57.5 ?/km (with 0.34 mm² conductor cross section)
<= 39 ?/km (with 0.5 mm² conductor cross section)
Nominal voltage, cable 250 V (AC)
Test voltage 2000 V (50 Hz, 5 minutes)
Smallest bending radius, fixed installation 20 mm
Smallest bending radius, movable installation 30....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12FR/ 8,0-PUR/M12FR VW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.