INDUSTRIAL COMPONENT DATA

SAC-5P-M12FS/ 0,2-920/M12FR 1094389 PHOENIX CONTACT Bus system cable, CANopen

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12FS/ 0,2-920/M12FR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12FS/ 0,2-920/M12FR
Catalog number	1094389
Category	Patch cord copper (twisted pair)
Minimum order	50 Pcs
Document ID	EO-C2452AC972
Generated	2026-11-18

Product Overview

Bus system cable, CANopen
Bus System Cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, Straight female M12, coding: A, to Elbow female M12, coding: A, cable length: 0.2 m
Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Socket straight M12, coding: A, on Socket angled M12, coding: A, cable length: 0.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
Sensor type CANopen®
Number of positions 5
No. of cable outlets 1
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
InterfacesBus system CANopen®/DeviceNet™
Signal type/category CANopen®
DeviceNet™

SignalingStatus display no
Status display present No
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
Material specificationsFlammability rating according to UL 94 HB
ConnectorConnection 1
Type Socket straight M12
Number of positions 5
Coding type A (Standard)
Connection 2
Type Socket angled M12
Number of positions 5
Coding type A (Standard)
Cable/lineCable length 0.2 m
CANopen®/DeviceNet™, PUR, violet [920]
Dimensional drawing
Cable weight 90 kg/km
UL AWM Style 21198 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type CANopen®/DeviceNet™, PUR, violet [920]
Conductor structure 2xAWG24/19+2xAWG22/19
Conductor structure signal line 19x 0.13 mm
AWG signal line 24
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
Wire diameter incl. insulation 1.95 mm ±0.05 mm (Data cable)
1.4 mm ±0.05 mm (Power supply)
External cable diameter 6.70 mm ±0.3 mm
Outer sheath, material PUR
External sheath, color red lilac RAL 4001
Conductor material Tin-plated Cu litz wires
Material wire insul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12FS/ 0,2-920/M12FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.