INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/0,6-PUR/M12FS BK 1055625 PHOENIX CONTACT Sensor/actuator cable SAC-5P-M12MR/0,6-PUR/M12FS BK 10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MR/0,6-PUR/M12FS BK

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MR/0,6-PUR/M12FS BK
Catalog number	1055625
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-C1AE99B4F5
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-5P-M12MR/0,6-PUR/M12FS BK - 1055625
Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Elbowed male connector M12, coding: A, to Straight connection female M12, coding: A, cable length: 0.6 m, with black grip body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12, A-coded, on Socket straight M12, A-coded, cable length: 0.6 m, with black grip
Key Commercial Data
Orderkey 1055625
Packing unit 1
GTIN 4055626692777
Custom tariff number 85444290
Dimensions
Length of cable 0.6 m
General
Number of positions 5

Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation approx. 0.5 mm
Wire colors brown, white, blue, black, green-yellow
External sheath, color black-gray RAL 7021
External cable diameter D 4.55 mm ±0.15 mm
Smallest bending radius, fixed installation 23 mm
Smallest bending radius, movable installation 46 mm
Number of bending cycles 10000000
Bending radius 50 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 33 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance >= 16 G?*km (at 20 °C)
Conductor resistance max. 58 ?/km (at 20 °C)
Nominal voltage, cable 300 V
Test voltage, cable 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
flexible
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Halogen-free in acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MR/0,6-PUR/M12FS BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.