INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/ 2,0-515 1423838 PHOENIX CONTACT Sensor/actuator cable SAC-5P-M12MR/ 2,0-515 1423838

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MR/ 2,0-515



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MR/ 2,0-515
Catalog number	1423838
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9677E4EAF1
Generated	2026-11-18

Product Overview

Sensor/actuator cable - SAC-5P-M12MR/ 2,0-515 - 1423838
Sensor/actuator cable, 5-pole, PVC, black RAL 9005, M12 angled connector, coding: A, to free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PVC, black RAL 9005, cable length: 2 m
Key Commercial Data
Orderkey 1423838
Packing unit 1
GTIN 4055626356815
Custom tariff number 85444290
Dimensions
Length of cable 2 m
Stripping length of the free conductor end 50 mm
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5

Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PVC black 5th conductor gray
Cable type (abbreviation) 515
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.45 mm ±0.02 mm
Thickness, insulation >= 0.23 mm (Core insulation)
>= 0.76 mm (Outer cable sheath)
Wire colors Brown, white, blue, black, gray
Overall twist 5 wires around filler to the core
Length of twist, overall twist 60 mm
External sheath, color black RA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MR/ 2,0-515 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.