INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/0,3-PUR/AD-2L 1439609 PHOENIX CONTACT Cable for sensors/actuators 5-pin, male Connector straigh..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/0,3-PUR/AD-2L

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/0,3-PUR/AD-2L
Catalog number	1439609
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E93335E9B0
Generated	2026-11-19

Product Overview

Cable for sensors/actuators 5-pin, male Connector straight M12, a coded, On valve Connector AD (pressure switch), with 2 LEDS, cable length: 0.3 m
Sensor/actuator cable, 5-pole, M12 straight connector, coding: A, to AD valve connectors (Druckschalter), with 2 LEDs, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensor / actuator, 5-pin,, PUR halogen-free, dark gray RAL 7021, Plug straight M12, A-coding, to Plug type AD to the solenoid valve (pressure switch), with 2 led, cable length: 0.3 m
Commercial data
Order code One million four hundred thirty nine thousand six hundred nine
Packaging unit 1 stk
GTIN Four trillion forty six billion three hundred fifty six million four hundred eighty nine thousand four hundred fifty four
Weight/PCs (without packing) 47,500 GRM
Dimensions
Cable length 0.3 m
General information
Rated voltage 24 V AC
24 V DC

Poles Five
Standards/normative documents M12 connector IEC 61076-2-101
Connectors for valve EN 175301-803
Cycles installation >= 100
Standards and regulations
The designation of the standard M12 Connector
Standards / normative documents IEC 61076-2-101
The designation of the standard Connectors for valves
Standards / normative documents EN 175301-803
Cable
Cable type PUR zero halogen black
Cable type (short designation) polyurethane
Symbol cable Li9Y11Y-HF
UL AWM Style Twenty thousand five hundred forty nine
Wire cross-section 5x 0,5 mm2
AWG signal line Twenty
Cable design, the signal line 28x 0.15 mm
Conductor diameter incl. insulation 1.5 mm ±0.05 mm (Signal wire)
Color lived black 1, black 2, black 3, black 4, green/yellow
General twisting 5 lived in the strand
Outer shell, color dark gray RAL 7021
Outer diameter of cable D 5.3 mm ±0.02 mm
Minimum bending radius when laying hard 26.5 mm
Minimum bending radius, when the movable space...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/0,3-PUR/AD-2L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.