INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/2,0-PUR/M8SIFSBBK 1421947 PHOENIX CONTACT Sensor/actuator cable SAC-5P-M12MS/2,0-PUR/M8SIFSBBK ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/2,0-PUR/M8SIFSBBK

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/2,0-PUR/M8SIFSBBK
Catalog number	1421947
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-CFC06F47CF
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/2,0-PUR/M8SIFSBBK - 1421947
Sensor/actuator cable, 5-pole, halogen-free PUR, grayish black RAL 7021, Straight male connector M12, coding: A, to Straight connection female M8 Snap-in, coding: B, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Socket straight M8 Snap-in, B-coded, cable length: 2 m
Key Commercial Data
Orderkey 1421947
Packing unit 1
GTIN 4055626288048
Custom tariff number 85444290
Dimensions
Length of cable 2 m
General
Rated current at 40°C 4 A

Rated voltage 30 V AC
30 V DC
Number of positions 5
Insulation resistance >= 100 M?
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR, black, 5th conductor gray
Cable type (abbreviation) 115
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 5x 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire colors Brown, white, blue, black, gray
Overall twist 5 cores, twisted
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.7 mm
External cable diameter D 5 mm ±0.15 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Number of bending cycles 4000000
Bending radius 50 mm
Traver...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/2,0-PUR/M8SIFSBBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.