INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 4,1-PUR/M12FS VA 1426372 PHOENIX CONTACT Cable for sensors/actuators

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 4,1-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 4,1-PUR/M12FS VA
Catalog number	1426372
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-3E0FE94CE9
Generated	2026-11-19

Product Overview

Cable for sensors/actuators
Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 4.1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators, 5-pole, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coded, cable length: 4,1 m
Data commercial
Key order One million four hundred twenty six thousand three hundred seventy two
Packing unit 1 pcs
Key selling BF1CDA -
Minimum order quantity 100 pcs
EAN Four trillion fifty five billion six hundred twenty six million four hundred fifty nine thousand sixty six
Unit weight (excluding packaging) 159,400 g
Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety
Measures
Cable length 4,1 m
Overview
Current sizing at 40 °C 4 To

Tension sizing 48 V AC
60 V DC
Number of poles Five
Insulation resistance >= 100 M?
Encoding A - standard
Status indication Not
Category surge II
Pollution degree Three
Cycles of plug >= 100
Material
Class of flammability according to UL 94 HB
Material contact CuSn
Material contact surface Ni/Au
Material support of contacts TPU GF
Material body grip TPU fire-retardant, self-extinguishing
Material knurled Stainless steel
Material of the board NBR
Standards and specifications
Class of flammability according to UL 94 HB
Cable
Type of cable PUR halogen-free black
Cable type (abbreviation) PUR
Abbreviation of cable Li9Y11Y
UL AWM Style 20549 / 10493 (80 °C/300 V)
Section of driver 5x 0,34 mm2 (driver signals)
Signal cable AWG Twenty two
Construction of the driver signal cable 42x 0.10 mm
Diameter of the conductors, insulation included 1.27 mm ±0.02 mm (driver signals)
Thickness of wall Ins...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 4,1-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.