INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/8,6-PUR/M12FS VA 1107927 PHOENIX CONTACT Sensor/actuator cable, 5-position, PUR halogen-free, b..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/8,6-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/8,6-PUR/M12FS VA
Catalog number	1107927
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-57A43605EF
Generated	2026-11-18

Product Overview

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 8.6 m, High-grade steel knurl
Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, M12 straight male connector, encoding: A, to M12 straight connection female, encoding: A, cable length: 8.6 m, Stainless steel knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1107927
Packing unit 1
GTIN 4063151010676
Custom tariff number 85444290
Drawings
General
Standards and Regulations
Classifications
Dimensions

Material
Cable
Drawings
Dimensional drawing
Plug, M12 x 1, straight
Dimensional drawing
M12 x 1 socket, straight
Circuit diagram
Contact assignment of the M12 plug and the M12 socket
Schematic diagram
Pin assignment M12 male connector, 5-pos., A-coded, male side
Schematic diagram
Pin assignment M12 socket, 5-pos., A-coded, socket side view
Cable cross section
PUR halogen-free black [PUR]
Back to topDimensions
Length of cable 8.6 m
Back to topGeneral
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Back to topMaterial
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Back to topStandards and Regulations
Flammability rating according to UL 94 HB
Back to topCable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/8,6-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.