INDUSTRIAL COMPONENT DATA

SAC-5P-M12MSL/ 1,5-280 FE SH 1414884 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MSL/ 1,5-280 FE SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MSL/ 1,5-280 FE SH
Catalog number	1414884
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-C3334CAE98
Generated	2026-11-19

Product Overview

Power cable
Power cable, 5-pole halogen-free, shielded (Advanced Shielding Technology), Straight M12 connector, coding: L, to free cable end, cable length: 1.5 m, for direct current up to 16 A / 63 V
Power cable, 5-position, PUR halogen-free, gray RAL 7001, shielded (Advanced Shielding Technology), Plug straight M12, coding: L, on free cable end, cable length: 1.5 m, for direct current up to 16 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Power cable
Application Power supply
Number of positions 5
No. of cable outlets 1
Shielded yes
Coding L
Data management status
Article revision 06
Insulation characteristics
Overvoltage category III
Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0
Material of grip body PP
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 63 V DC
Nominal current IN 16 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
ConnectorConnection 1
Type Plug straight M12
Coding type L (Power)
Connection 2
Type free cable end
Cable/lineCable length 1.5 m
PUR halogen-free gray [280]
Dimensional drawing
Cable weight 202 kg/km
UL AWM Style 20233 / 10493 (80°C/300 V)
Number of positions 5
Shielded yes
Cable type PUR halogen-free gray [280]
Conductor cross section 5x 2.5 mm²
Wire diameter incl. insulation 2.85 mm ±0.1 mm
External cable diameter 10.40 mm ±0.3 mm
Outer sheath, material PUR
External sheath, color gray RAL 7001
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black, pink
Thickness, insulation >= 0.31 mm
Thickness, outer sheath approx. 0.76 mm
Max. conductor resistance <= 8 ?/km (at 20 °C)
Insulation resistance >= 1 G?*km (at 20 °C)
Nominal voltage, cable <= 300 V AC
Test voltage >= 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MSL/ 1,5-280 FE SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.