INDUSTRIAL COMPONENT DATA

SAC-5P-M8MSB/0,5-115/M8SIFSB 1030294 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M8MSB/0,5-115/M8SIFSB

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M8MSB/0,5-115/M8SIFSB
Catalog number	1030294
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-3DB16FC229
Generated	2026-11-19

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1030294
Packing unit 1
GTIN 4055626533704
Custom tariff number 85444290
Dimensions
Length of cable 0.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
General
Rated current at 40°C 3 A
Rated voltage 30 V
Number of positions 5
Insulation resistance >= 100 M?
Coding B - inverse

Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) 115
Cable abbreviation Li9Y11Y
UL AWM style 20549
Conductor cross section 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation approx. 0.21 mm (Core insulation)
approx. 0.7 mm (Outer cable sheath)
Wire colors Brown, white, blue, black, gray
Overall twist 5 cores, twisted
Length of twist, overall twist 75 mm
External sheath, color black-gray RAL 7021
External cable diameter D 4.7 mm ±0.15 mm
Smallest bending radius, fixed installation 23.5 mm
Smallest bending radius, movable installation 47 mm
Number of bending cycles 4000000
Bending radius 47 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cabl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M8MSB/0,5-115/M8SIFSB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.