INDUSTRIAL COMPONENT DATA

SAC-5PY-F/2X 0,3-920-MS-FS VA 1414230 PHOENIX CONTACT Bus system cable SAC-5PY-F/2X 0,3-920-MS-FS VA 1414230

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PY-F/2X 0,3-920-MS-FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PY-F/2X 0,3-920-MS-FS VA
Catalog number	1414230
Category	Data and communication cable
Minimum order	50 Pcs
Document ID	EO-BE65A6AA45
Generated	2026-11-19

Product Overview

Bus system cable - SAC-5PY-F/2X 0,3-920-MS-FS VA - 1414230
Bus System Cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, Straight female M12, coding: A, a Straight female M12, coding: A and Straight connector M12, coding: A, cable length: 0.3 m, all pluggable connectors unshielded, The display is positioned above pin 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, violet RAL 4001, shielded, Socket straight M12, A-coded, on Socket straight M12, A-coded and Plug straight M12, A-coded, cable length: 0.3 m, all connectors unshielded, Shield connected to pin 1
Key Commercial Data
Orderkey 1414230
Packing unit 1
GTIN 4055626020648
Custom tariff number 85444290
Dimensions
Length of cable 0.3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Signal type/category CANopen®
DeviceNet™
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type CAN Bus/DeviceNet
Cable type (abbreviation) 920
UL AWM style 21198 (80°C/300 V)
Cable structure 2xAWG24/19+2xAWG22/19
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.13 mm
Conductor structure, voltage supply 19x 0.15 mm
Core diameter including insulation 1.95 mm ±0.05 mm (Data cable)
1.4 mm ±0.05 mm (P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PY-F/2X 0,3-920-MS-FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.