INDUSTRIAL COMPONENT DATA

SAC-8P- 0,3-PUR/M 8FR 1130344 PHOENIX CONTACT Cable para sensores/actuadores, 8-polos, PUR sin halógenos, ne..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-0,3-PUR/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-0,3-PUR/M 8FR
Catalog number	1130344
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-C35DE8B877
Generated	2026-11-19

Product Overview

Cable para sensores/actuadores, 8-polos, PUR sin halógenos, negro grisáceo RAL 7021, longitud de cable: 0,3 m
Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Elbowed connection female M8, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1130344
Packing unit 1
GTIN 4063151060015
Custom tariff number 85444290
Drawings
General
Standards and Regulations
Environmental Product Compliance
Dimensions
Material
Cable
Classifications

Drawings
Dimensional drawing
Socket M8 x 1, angled
Circuit diagram
Contact assignment of M8 socket
Schematic diagram
Connector pin assignment of M8 socket, 8-pos., view of socket side
Cable cross section
PUR halogen-free black [PUR]
Back to topDimensions
Length of cable 0.3 m
Back to topGeneral
Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Degree of pollution 3
Back to topMaterial
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Back to topStandards and Regulations
Standards/specifications M8 connector IEC 61076-2-104
Flammability rating according to UL 94 HB
Back to topCable
Cable abbreviation Li9Y11Y
UL AWM style 20549
Conductor cross section 8x 0.14 mm² (Signal line)
AWG signal line 26
Conductor structure signal line 18x 0.10 mm
Core diameter including insulation 1 mm ±0.02 mm (Signal line)
Thickness, insulation >= 0.21 mm (Signal line)
>= 0.38 mm (Outer cable sheath)
Wire colors white...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-0,3-PUR/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.