INDUSTRIAL COMPONENT DATA

SAC-8P-10,0-PUR/M12FS VA 1412465 PHOENIX CONTACT Sensor/actuator cable SAC-8P-10,0-PUR/M12FS VA 1412465

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-10,0-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-10,0-PUR/M12FS VA
Catalog number	1412465
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-AFC1E18055
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-8P-10,0-PUR/M12FS VA - 1412465
Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Number of positions 8
No. of cable outlets 1
Shielded no
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuZn
Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Stainless steel
Outer sheath, material PUR
Conductor material Bare Cu litz wires
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 2 A
Max. conductor resistance 78 ?/km
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 8
Coding type A
Cable/lineCable length 10 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 46 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 8
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 8x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm ±0.02 mm
External cable diameter 5.90 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material, filler PE
Material wire insulat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-10,0-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.