INDUSTRIAL COMPONENT DATA

SAC-8P-20,0-28X/M12FS OD 1423789 PHOENIX CONTACT Sensor/actuator cable SAC-8P-20,0-28X/M12FS OD 1423789

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-20,0-28X/M12FS OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-20,0-28X/M12FS OD
Catalog number	1423789
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-114D84E086
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-8P-20,0-28X/M12FS OD - 1423789
Sensor/Actuator Cable, 8-Pole, Halogen-Free, Black-Grey RAL 7021, Free Cable End, to Straight Connecting Female M12, Coding: A, Cable Length: 20 m, For Outdoor Applications, With Stainless Steel Knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 8-position, PE-X halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 20 m, for outdoor applications, with high-grade steel knurl
Key Commercial Data
Orderkey 1423789
Packing unit 1
GTIN 4055626353364
Custom tariff number 85444290
Dimensions
Length of cable 20 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)
-40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4))
General

Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FPM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 V0
Cable
Cable type PE-X black
Cable type (abbreviation) 28X
Cable abbreviation Li2X2X
Conductor cross section 8x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation approx. 0.25 mm (Core insulation)
Wire colors white, brown, green, yellow, gray, pink, blue,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-20,0-28X/M12FS OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.