INDUSTRIAL COMPONENT DATA

SAC-8P-M12FS/35,0-PUR/M12FS SH 1576520 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12FS/35,0-PUR/M12FS SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12FS/35,0-PUR/M12FS SH
Catalog number	1576520
Category	Patch cord copper (twisted pair)
Minimum order	25 Pcs
Document ID	EO-E489F4A65E
Generated	2026-11-19

Product Overview

Bus system cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1576520
Packing unit 1
GTIN 4046356520836
Custom tariff number 85444290
Dimensions
Length of cable 7 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
-20 °C ... 70 °C (RJ45)
Degree of protection IP20
General
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC

Number of positions 6
Coding A - standard
Signal type/category VARAN
Status display No
Overvoltage category I
Degree of pollution 1
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Additional material specifications PC (RJ45 contact carrier material)
PA (RJ45 housing material)
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type VARAN
Cable type (abbreviation) 970
Cable abbreviation Li9YD12Y
Cable structure 1x2xAWG22/19 + 1x4xAWG24/19
Conductor cross section 4x 0.25 mm² (Signal line)
2x 0.38 mm² (Power supply)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.13 mm
Conductor structure, voltage supply 19x 0.16 mm
Core diameter including insulation 1.35 mm (Signal line)
1.5 mm (Power supply)
Wire colors Brown, blue, white/orange, white/green, green, orange
Type of pair shielding Tinned copper braided shield, 95 % covering
Overall twist 1 star quad and 2 wires with 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12FS/35,0-PUR/M12FS SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.