INDUSTRIAL COMPONENT DATA

SAC-8P-MR/ 2,0-PUR/FR SCO BK 1419201 PHOENIX CONTACT Sensor/actuator cable SAC-8P-MR/ 2,0-PUR/FR SCO BK 1419..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-MR/ 2,0-PUR/FR SCO BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-MR/ 2,0-PUR/FR SCO BK
Catalog number	1419201
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-799419C6F4
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-8P-MR/ 2,0-PUR/FR SCO BK - 1419201

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, shielded, cable length: 2 m
Key Commercial Data
Orderkey 1419201
Packing unit 1
GTIN 4055626157184
Custom tariff number 85444290
Dimensions
Length of cable 2 m
General
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8

Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LiF9YC11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 8x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation approx. 0.2 mm
Wire colors Brown, white, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
Shielding Tinned copper braided shield
Optical shield covering 85 %
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 5.9 mm ±0.2 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Number of bend...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-MR/ 2,0-PUR/FR SCO BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.