INDUSTRIAL COMPONENT DATA

SAC-8P-M12MS/ 3,0-542/M12FSSH 1417921 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12MS/ 3,0-542/M12FSSH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12MS/ 3,0-542/M12FSSH
Catalog number	1417921
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-10DFE7B39C
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Cable for sensors/actuators, 8-pole, PVC, yellow, shielded, Straight male connector M12, coding: A, to Straight connection female M12, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1417921
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626211367
Weight per Piece (excluding packing) 22.220 g
Country of origin US (United States)
Dimensions
Length of cable 3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67

General
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Color handle area black
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PVC yellow 105 °C
Cable type (abbreviation) 542
UL AWM style 2517 (105 °C / 300 V)
AWG signal line 24
Conductor structure signal line 32x 1.10 mm
Core diameter including insulation 1.12 mm ±0.03 mm
Wire colors white, brown, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
Shielding Tinned copper braided shield
Optical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12MS/ 3,0-542/M12FSSH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.