INDUSTRIAL COMPONENT DATA

SAC-8P-MS/30,0-280/FS SH SCO 1419497 PHOENIX CONTACT Sensor/actuator cable SAC-8P-MS/30,0-280/FS SH SCO 1419..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-MS/30,0-280/FS SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-MS/30,0-280/FS SH SCO
Catalog number	1419497
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E2F222E25E
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-8P-MS/30,0-280/FS SH SCO - 1419497

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 8-position, PUR halogen-free, gray RAL 7001, shielded, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded, cable length: 30 m
Key Commercial Data
Orderkey 1419497
Packing unit 1
GTIN 4055626168852
Custom tariff number 85444290
Dimensions
Length of cable 30 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67
General
Rated current at 40°C 2 A

Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free gray
Cable type (abbreviation) 280
Cable abbreviation LiY-FC11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 8x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation approx. 0.2 mm
Wire colors Brown, white, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
Shielding Tinned copper braided shield
Optical shield covering 85 %
External sheath, c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-MS/30,0-280/FS SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.