INDUSTRIAL COMPONENT DATA

SAC-8P-MS/ 3,5-PUR/MS SH SCO 1403872 PHOENIX CONTACT Cable for sensors/actuators SAC-8P-MS/ 3,5-PUR/MS SH SC..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-MS/ 3,5-PUR/MS SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-MS/ 3,5-PUR/MS SH SCO
Catalog number	1403872
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-229874193A
Generated	2026-11-19

Product Overview

Cable for sensors/actuators - SAC-8P-MS/ 3,5-PUR/MS SH SCO - 1403872
Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 SPEEDCON straight male connector, to M12 SPEEDCON straight male connector, cable length: 3.5 m
Sensor/actuator cable, 8-pin, halogen-free, grey-black RAL 7021, shielded, straight male M12 SPEEDCON, coding: A, on straight male M12 SPEEDCON, cable length: 3.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators, 8-pole, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12 SPEEDCON, on Plug straight M12 SPEEDCON, cable length: 3.5 m
Data commercial
Key order One million four hundred three thousand eight hundred seventy two
Packing unit 1 pcs
Key selling BF1CMA -
EAN Four trillion forty six billion three hundred fifty six million six hundred seventy one thousand nine hundred fifty eight
Unit weight (excluding packaging) 214,300 g
Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Measures
Cable length 3.5 m
Environmental conditions
Room temperature (service) -25 °C ... 90 °C (male / female)
Index of protection IP65
IP67
Overview
Current sizing at 40 °C 2 To
Tension sizing 30 V AC
30 V DC
Number of poles Eight
Insulation resistance >= 100 M?
Encoding A - standard
Status indication Not
Category surge II
Pollution degree Three
Tightening torque 0.4 Nm (M12 Connector)
Material
Class of flammability according to UL 94 HB
Material contact CuZn
Material contact surface Ni/Au
Material support of contacts TPU GF
Material body grip TPU fire-retardant, self-extinguishing
Material knurled Die-cast zinc, nickel plated
Material of the board NBR
Standards and specifications
Class of flammability according to UL 94 HB
Cable
Type of cable PUR halogen-free black
Cable type (abbreviation) PUR
Abbreviation of cable LiF9YC11Y
UL AWM Style 20549 / 10493 (80 °C/300 V)
Section of driver 8x 0.25 mm2 (driver signals)
Signal cab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-MS/ 3,5-PUR/MS SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.