INDUSTRIAL COMPONENT DATA

SAC-8P-MS/ 3,5-PUR SH SCO 1426523 PHOENIX CONTACT Cable for sensors/actuators, 8-pole, PUR halogen-free, bla..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-MS/ 3,5-PUR SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-MS/ 3,5-PUR SH SCO
Catalog number	1426523
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-F81F1741C3
Generated	2026-11-19

Product Overview

Cable for sensors/actuators, 8-pole, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12 SPEEDCON, coded, to the end of free cable, cable length: 3.5 m
Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 SPEEDCON straight male connector, coding: A, to free cable end, cable length: 3.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable, sensor-actuator, 8-pin, PUR without halogenated, black-grey RAL 7021, shielded, straight Male M12 SPEEDCON, A-coded, on the ends of conductor the free, cable length: 3.5 m
Commercial data
The code for the order One million four hundred twenty six thousand five hundred twenty three
Pieces/pack. 1 PCS
Sales key BF1CMA -
The amount of minimum order 25 PCS
GTIN Four trillion fifty five billion six hundred twenty six million four hundred sixty three thousand one
Weight per piece (package included) 22,220 g
Number customs tariff Eighty five million four hundred forty four thousand two hundred ninety
Size
Length. cable 3.5 m

Environmental conditions
Ambient temperature (operation) -25 °C ... 90 °C (plug / connector female)
General
Rated current at 40 °C Two
Rating voltage 30 V AC
30 V DC
N. of poles Eight
Insulation resistance >= 100 M?
Encoding A - standard
Rules/Provisions M12 connector IEC 61076-2-101
Signalling status of No
Circuit/component protection without circuit
Overvoltage category II
Pollution degree Three
Number of operating cycles, >= 100
Material
Class behaviour according to UL 94 HB
Contact material CuZn
Material surface contacts Ni/Au
Insert material latch TPU GF
Material handles TPU, hardly inflammable, self-extinguishing
Nut material Zinc die-cast, nickel-plated
Regulations and requirements
Definition standard M12 Connector
Rules/Provisions IEC 61076-2-101
Class behaviour according to UL 94 HB
Cable
Cable type EVEN without halogenated black
Cable type (abbrev...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-MS/ 3,5-PUR SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.