INDUSTRIAL COMPONENT DATA

SAC-8PY-M/0,15-285/FR-F VP SCO 1403384 PHOENIX CONTACT Y-distributor, 8-pos., shielded, straight M12 SPEEDCO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8PY-M/0,15-285/FR-F VP SCO

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8PY-M/0,15-285/FR-F VP SCO
Catalog number	1403384
Category	Sensor actuator adapter
Minimum order	150 Pcs
Document ID	EO-4C5DE3F074
Generated	2026-11-19

Product Overview

Y-distributor, 8-pos., shielded, straight M12 SPEEDCON plug (A-coded) to angled M12 SPEEDCON socket (A-coded), with shielded PUR cable, length: 0.15 m, and straight M12 SPEEDCON socket (A-coded)
Y Splitter, 8 poles, pant., female connection. Rec. M12 SPEEDCON, codif. A, in female connection. acod. M12 SPEEDCON, codif. A, c. PUR duct pant., length: 0.15 m and rec male connector. M12 SPEEDCON, codif. To

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1403384
Packing unit 1
GTIN 4046356651462
Custom tariff number 85444290
Drawings
Ambient conditions
Material
Cable
Classifications

Dimensions
General
Standards and Regulations
Environmental Product Compliance
Drawings
Circuit diagram
Contact assignment of the M12 Y distributor
Schematic diagram
Pin assignment M12 plug, 8-pos., A-coded, view plug side
Schematic diagram
Pin assignment M12 socket, 8-pos., A-coded, view female side
Cable cross section
PUR, gray, shielded [285]
Back to topDimensions
Length of cable 0.15 m
Back to topAmbient conditions
Degree of protection IP65
IP67
Back to topGeneral
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Back to topMaterial
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Back to topStandards and Regulations
Standards/specifications M12 connector
Flammability rating according to UL 94 HB
Back to topCable
Cable type PUR, gray, shielded
Cable type (abbreviation) 285
Cable abbreviation Li12YC11Y-HF
Conductor cross section 4x 2x 0.25 mm² (Signal line)
1x 0.25 mm² (Drain wire)

AWG signal line 24...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8PY-M/0,15-285/FR-F VP SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.