INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSDR-4CON-L90 THR R 1028581 PHOENIX CONTACT Flush-type socket SACC-CI-M12FSDR-4CON-L90 THR R 1028..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSDR-4CON-L90 THR R



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSDR-4CON-L90 THR R
Catalog number	1028581
Category	Contact insert for circular connectors
Minimum order	120 Pcs
Document ID	EO-A5DE2821AC
Generated	2026-11-19

Product Overview

Flush-type socket - SACC-CI-M12FSDR-4CON-L90 THR R - 1028581
Built-in Mount Female, 4-Pole, Connecting Female, Elbow, Encoding: D, Printed Circuit Board Mounting, THR Solder Connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Flush-type socket, 4-position, Socket, angled, D-coded, PCB mounting, Solder pins
Key Commercial Data
Orderkey 1028581
Packing unit 1
GTIN 4055626666082
Custom tariff number 85366990
Ambient conditions
Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)
-40 °C ... 105 °C (without mechanical actuation)
Degree of protection IP67
General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Not compatible with SPEEDCON housings.
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding D-coded
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type PCB mounting The pin assignment is rotated 180° to comply with the standard.
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Cable
Standards/specifications M12 connector IEC 61076-2-101
Ambient temperature (operation) -40 °C ... 105 °C (cable, fixed installation)
-25 °C ... 105 °C (cable, flexible insta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSDR-4CON-L90 THR R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.