INDUSTRIAL COMPONENT DATA

SACC-CI-M12MSR-4CON-L90 THR R 1028588 PHOENIX CONTACT Flush-type connector, 4-position, Plug, angled, A-code..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12MSR-4CON-L90 THR R



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12MSR-4CON-L90 THR R
Catalog number	1028588
Category	Contact insert for circular connectors
Minimum order	120 Pcs
Document ID	EO-A7A208B712
Generated	2026-11-18

Product Overview

Flush-type connector, 4-position, Plug, angled, A-coded, PCB mounting, Solder pins
Contact Holder, 4-Pole, Male Connector, Elbowed, Coding: A, Printed Circuit Board Mounting, THR Solder Connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1028588
Packing unit 1
GTIN 4055626666204
Custom tariff number 85366990
Ambient conditions
Material
Standards and Regulations
Classifications
General
Cable
Environmental Product Compliance

Ambient conditions
Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)
-40 °C ... 105 °C (without mechanical actuation)
Degree of protection IP67
Back to topGeneral
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Not compatible with SPEEDCON housings.
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding A-coded
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type PCB mounting The pin assignment is rotated 180° to comply with the standard.
Back to topMaterial
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Back to topCable
Standards/specifications M12 connector IEC 61076-2-101
Back to topStandards and Regulations
Standards/spe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12MSR-4CON-L90 THR R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.