INDUSTRIAL COMPONENT DATA

SACC-CIM12MS17PL180THRSHSAMPLE 1413555 PHOENIX CONTACT Sample set SACC-CIM12MS17PL180THRSHSAMPLE 1413555

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CIM12MS17PL180THRSHSAMPLE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CIM12MS17PL180THRSHSAMPLE
Catalog number	1413555
Category	Contact insert for circular connectors
Minimum order	1 Pcs
Document ID	EO-39A2429074
Generated	2026-11-19

Product Overview

Sample set - SACC-CIM12MS17PL180THRSHSAMPLE - 1413555
Male assembly incorp. p/ sensors/actuators, 17 poles, with screen plate, codif. A, with straight THR welding connection, contact insert only

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Sensor/actuator flush-type plug, 17-pos. with shroud, A-coded, with straight THR solder connection, contact insert only
Key Commercial Data
Orderkey 1413555
Packing unit 1
GTIN 4055626008257
Custom tariff number 85366990
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 1.5 A
Rated voltage 30 V
Rated surge voltage 0.8 kV
Number of positions 17
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category III
Degree of pollution 3
Connection method THR solder connection
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type PCB mounting
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PPA
Cable
Standards/specifications M12 connector IEC 61076-2-101
Ambient temperature (operation) -40 °C ... 85 °C (cable, fixed installation)
-25 °C ... 85 °C (cable, flexible installation)
Standards and Regulations
Standard designatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CIM12MS17PL180THRSHSAMPLE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.