INDUSTRIAL COMPONENT DATA

SACC-CIP-M8FS-8P SMD SH R32 1412262 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CIP-M8FS-8P SMD SH R32



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CIP-M8FS-8P SMD SH R32
Catalog number	1412262
Category	Contact insert for circular connectors
Minimum order	120 Pcs
Document ID	EO-AA5CED569D
Generated	2026-11-19

Product Overview

Flush-type connector
Plug-in Connector Mounting Insert, 8-Pole, Female Connection, Straight, M8, A-Coded, Printed Circuit Board Mounting, SMD, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) 1238991

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1412262
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4046356989039
Weight per Piece (excluding packing) 5.980 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)
-40 °C ... 105 °C (without mechanical actuation)
Degree of protection IP67 (correctly plugged in and locked)

General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance <= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Overvoltage category II
Connection method SMD
Insertion/withdrawal cycles > 100
Mounting type PCB mounting
Type of packaging Belt
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Sealing material FKM
Cable
Standards/specifications M8 connector IEC 61076-2-104
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CIP-M8FS-8P SMD SH R32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.