INDUSTRIAL COMPONENT DATA

# SACC-CIP-M8MS-3P SMD SH R32X 1308281 PHOENIX CONTACT Contact holder, 3-pole, Male connector, straight, M8, c..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CIP-M8MS-3P SMD SH R32X**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SACC-CIP-M8MS-3P SMD SH R32X |
| Catalog number | 1308281 |
| Category | Contact insert for circular connectors |
| Minimum order | 100 Pcs |
| Document ID | EO-FE2F105CA5 |
| Generated | 2026-11-19 |

## Product Overview

Contact holder, 3-pole, Male connector, straight, M8, coding: A, Printed circuit board mounting, SMD reflow, The item does not contain lead according to the RoHS II directive without the exception 6c (Pb&lt.; 0.1%)
Contact Holder, 3-Pole, Male Connector, Straight, M8, Coding: A, Printed Circuit Board Mounting, SMD Reflow, RoHS II Lead-Free Article without 6c (Pb< 0.1%) exception
Contact carrier, 3-position, Pin, straight, M8, coding: A, PCB mounting, SMD reflow, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT |

## Additional Product Information

Technical dataNotesGeneral The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Product propertiesProduct type Contact insert
Number of positions 3
Application Signal
Seal present yes

Shielded yes
Coding A
Thread type M8
Insulation characteristics
Overvoltage category III
Electrical propertiesContact resistance <= 3 m?
Insulation resistance <= 100 M?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Connection dataConnection method SMD reflow
Cross section AWG (converted acc. to IEC)
Material specificationsFlammability rating according to UL 94 V0
Seal material FKM
Contact material CuZn
Contact surface material Au
Contact carrier material PA
ConnectorConnection 1
Head design Pin
Head cable outlet straight
Head thread type M8
Coding A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles > 100
Environmental and real-life conditionsAmbient conditions
Degree of protection (when plugged in) IP67 (correctly plugged in and locked)
Degree of protection IP67
Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)
-55 °C ... 105 °C (without mechanical actuation)
Standards and regulationsStandard designation M8 connector
Standards/specifications IEC 61076-2-104
MountingMounting...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CIP-M8MS-3P SMD SH R32X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.