INDUSTRIAL COMPONENT DATA

SACC-CIP-M8MS-4P SMD SH T 1412241 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CIP-M8MS-4P SMD SH T



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CIP-M8MS-4P SMD SH T
Catalog number	1412241
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-E69C70B533
Generated	2026-11-19

Product Overview

Flush-type connector
Contact Holder, 4-Pole, Male, Straight, M8, Coding: A, Printed Circuit Board Mounting, SMD Reflow, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) Item Code: 1308266

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1412241
Packing unit 60 pc
Minimum order quantity 60 pc
Note Made to Order (non-returnable)
GTIN 4046356988834
Weight per Piece (excluding packing) 3.450 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)
-55 °C ... 105 °C (without mechanical actuation)
Degree of protection IP67 (correctly plugged in and locked)

General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 3 A
Rated voltage 50 V AC
60 V DC
Number of positions 4
Insulation resistance <= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Overvoltage category II
Connection method SMD
Insertion/withdrawal cycles > 100
Mounting type PCB mounting
Type of packaging Tray
Delivery state with assembly pad
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Sealing material FKM
Cable
Standards/specifications M8 connector IEC 61076-2-104
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 V0
Environmental....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CIP-M8MS-4P SMD SH T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.