INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FSL4CON-M16XL-L180 1425593 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FSL4CON-M16XL-L180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FSL4CON-M16XL-L180
Catalog number	1425593
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-1C4538A25A
Generated	2026-11-19

Product Overview

Flush-type connector
Conect. plug. to be apar. wall poster., Power, 4-pole, Connecting female, straight, M12, coding: L, Rear mounting, M16 x 1.5, Wave soldering, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239524
Rear device connector, Power, 4-pin, Socket, straight, M12, Code: L, Rear mounting, M16 x 1.5, Wave soldering, Alternative according to RoHS II without exception 6c (Pb < 0.1 %) Art. No.: 1239524

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1425593
Packing unit 20 pc
Minimum order quantity 20 pc
Note Made to Order (non-returnable)
GTIN 4055626428468
Weight per Piece (excluding packing) 17.640 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 16 A
Rated voltage 63 V
Rated surge voltage 1.5 kV
Number of positions 4
Coding L - Power
Standards/regulations M12 connector IEC 61076-2-111 In line with
Signal type/category Power
Overvoltage category III
Degree of pollution 3
Connection method Solder pins
Mounting type Rear mounting M16 x 1.5 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Material, knurls Zinc die-cast, nickel-plated
Additional material specifications PU 2K (Grout material)
Cable
Standards/specifications M12 connector IEC 61076-2-111 In line with
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-111
Fla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FSL4CON-M16XL-L180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.