INDUSTRIAL COMPONENT DATA

SACC-DSI-M12MSL-4FE-M16XL/0,2 1415297 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12MSL-4FE-M16XL/0,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12MSL-4FE-M16XL/0,2
Catalog number	1415297
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-61255E3107
Generated	2026-11-19

Product Overview

Flush-type connector
Conect. plug. to be apar. wall poster., Power, 5-pole, Male connector, straight, M12-Standard, coding: L, to free cable end, Rear mounting, M16 x 1.5, Single stranded wires, cable length: 0.2 m, 2.50 mm², PEX conductor, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239084

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1415297
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 292 (C-2-2017)
GTIN 4055626056265
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.2 m
Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
FE not connected to metal parts that can be touched, no protective function
Rated current at 40°C 16 A
Rated voltage 63 V
Rated surge voltage 1.5 kV
Number of positions 5
Coding L - Power
Standards/regulations M12 connector IEC 61076-2-111 In line with
Signal type/category Power
Overvoltage category III
Degree of pollution 3
Test voltage 1.5 kV
Connection method Individual wires
Torque 0.8 Nm ... 1.3 Nm (Installation-side)
Mounting type Rear mounting M16 x 1.5 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Material, knurls Zinc die-cast, nickel-plated
Sealing material FKM
Additional material specifications PU 2K (Grout material)
Cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12MSL-4FE-M16XL/0,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.